DVI-D KVM Switch

Optimize rack space. Maximize rack monitoring



F© (E 🖌

Features

•8 Port DVI-D, USB, Audio KVM.

- •DVI-D single link support resolution up to 1920x1200.
- •USB local console.
- •2x USB 2.0 ports sharing USB peripheral for computers.
- Mixed PCs, SUNs & MACs with multi-platform switch Capability.
- •Computer switching via push buttons, Hot keys.
- •Hot pluggable, no software or driver required.
- Easy and quick installation.



Rear of KDC-108

Part No.	KDC-108
No. of Computers	8
KVM port connector	DVI-D for Video USB 2.0 type B for KB/Mouse 3.5mm phone jack for Audio
Local Console	1x DVI-D for Video (up to 1920x1200 resolution) 2x USB Type A for KB / Mouse
USB HUB	2x USB 2.0 Type A for USB peripheral devices
Switching Port	Push button / Hot key
Compatibility	Mix PCs, SUNs and MACs, support Win7/Vista/2003/XP, Linux, Unix
Power	100-240V AC 50/60Hz external power adapter
Environment	Operation temp.: 0 to 50°C Storage temp : -20 to 60°C Humidity: 10% - 90%, non-condensing
Physical Dimensions /Net Weights	448mm (W) x 167mm (D) x 44mm (H) / 3kg
Packing Dimensions /Gross Weights	560*120*250mm / 3.5kg
Relate Items	
CD-018	1.8meter DVI Cable
CU-018	1.8meter USB Cable
CA-018	1.8meter Audio Cable

Specifications subject to change without notice



USA (Head Quarter) Denichi Computer Devices, Inc. 13200 Pond Springs Rd. #A102, Austin, TX 78729 Office: 512-837-2655 Fax: 512-837-1694 Email: sales@denichi.com China (Factory) Add : The south faces industry area of Xia Gang Fu Hai road, Chang'an Town, Dongguan City, Guangdong, China Email: sales@denichi.com